



TECHNICAL SPECIFICATIONS

SPECIFICATIONS ARE SUBJECT TO CHANGE



(Sizes in mm)	BAK G-51-53-E	BAK G-92-53-E	BAK G-132-53-E	BAK G-173-53-E
Outside dimension (represent outside flanges):				
Length x depth x height *)	515 x 770 x 530	920 x 770 x 530	1325 x 770 x 530	1730 x 770 x 530
PRO-Version: Length x depth x height *)	505 x 770 x 510	910 x 770 x 510	1315 x 770 x 510	1720 x 770 x 510
Cut-out size:				
Length x depth	495 x 745	905 x 745	1310 x 745	1715 x 745
Usable internal size:				
Length x depth x height	405 x 610 x 40	810 x 610 x 40	1215 x 610 x 40	1620 x 610 x 40
Display surface (in m ²)	0,43	0,84	1,26	1,68
❄️ Refrig. capacity evap. @ -10°C	370 Watt	420 Watt	480 Watt	600 Watt
Refrigerant	R 134a			
🌡️ Temperature range	+5°C			
💧 Relative humidity	approx. 70 - 85%			
Power consumption	390 Watt	561 Watt	587 Watt	651 Watt
🔌 Daily energy consumption	5,62 kW/24h	8,08 kW/24h	8,45 kW/24h	9,37 kW/24h
Voltage	230 V 50 Hz			

*) height of the glass top (without drop-in part)

Specification at +25°C ambient temperature and 60% RH (climate classification 3 acc. to DIN EN ISO 23953).